



Pressure Washer Turned or Flipped During Delivery Single Cylinder

Model Numbers:

STEP	ACTION	NOTE
1.	Drain oil from engine	There are 2 drain plugs on both sides of the engine block, remove either one- 10 or 12mm wrench needed.
2.	Drain fuel - DO NOT ADD FUEL if empty	No need to drain fuel - skip this step and proceed to next step. Units ship without fuel
3.	Remove air filter from air filter cover	Inspect paper filter and pre filter, replace if any oil is present (contact us for replacement filter) do not reinstall at this time.
4.	Remove drain bolt from carburetor bowl	10mm wrench needed, clean and set aside for now
5.	Remove sediment bowl located near carburetor bowl	10mm wrench needed, clean and set aside for now
6.	If any oil is present let drain and clean bowls	do not re-install at this time
7.	Remove spark plug	13/16" socket needed, clean and set aside
8.	Make sure on/off switch is in the off position	Caution: hold rag over spark plug hole, to avoid oil from spraying all over
9.	Pull cord until no more oil comes out of the cylinder.	This may take several attempts, keep going until no more oil is present.
10.	Clean spark plug free of oil or gas	
11.	Re-install spark plug	13/16" socket needed
12.	Re-install sediment bowl	10mm wrench needed
13.	Replace drain bolt to carburetor.	10mm wrench needed
14.	Re-install air filter	Replace if necessary
15.	Fill engine with oil to correct level	consult manual for correct level and grade
16.	Check and fill pump with oil to proper level	halfway on the sight glass or use oil dipstick check manual for correct level grade
17.	Hook up the water supply	do not connect the high pressure discharge hose at this time
18.	Turn on water Supply	make sure the water is running free from the unloader discharge.
19.	Add Gasoline	
20.	Start machine as normal	make sure the water is running free from hose or from the unloader
21.	Let the machine run until there's no smoke present	This may take several minutes depending how much oil got into the system
22.	If engine does not start there may be still more oil in cylinder	Re do previous steps until all oil is drained from cylinder



**Pressure Washer Turned or Flipped During Delivery
Single Cylinder**

Model Numbers: