

RK18.28HN Pump

18TRH43 5 GPM @ 4000 PSI

GX630 Engine

POWERED by
HONDA

TRAILER FEATURES

- 2- 250' high pressure hose reels
- · Chemical resistant coating
- 200 gallon water tank & Poly tool box
- · Lights, jack, w/ wheel & safety chains
- Fully tested and assembled in the USA
- HD trailer (forkliftable) 3500# capacity axle, 135"L x 82"W x 63"H
- Aluminum fenders, 15" wheels/tires, external grease fittings.

HOSE OPTIONS

AHS235 4000 PSI 3/8" X 100' Black W/Qc's
AHS240 4000 PSI 3/8" X 150' Black W/Qc's
AHS245PRO 4000 PSI 3/8" X 200' Black W/Qc's
AHS285 4000 PSI 3/8" X 100' Gray W/Qc's
AHS290PRO 4000 PSI 3/8" X 150' Gray W/Qc's
AHS295 4000 PSI 3/8" X 200' Gray W/Qc's
AHS335 6000 PSI 3/8" X 100' Black W/Qc's
988VR-100 3/4" X 100' HD Garden Hose

STANDARD FEATURES

- Rugged steel, low-profile frame with powder coated finish. 48"L x 40"W x 41"H frame dimensions
- Super efficient insulated schedule 80 coil
- Stainless steel coil wrap, burner hood, control panel
- 15 gallon poly diesel and gasoline fuel tanks with fuel filters
- Commercial/Industrial grade engines w/electric start
- Reliable Beckett burners
- Adjustable thermostat
- Safety pressure relief valve
- Four 3VX belt system offers balanced power transfer AVAILABLE OPTIONS

KTF200 Float valve kit.

KAV001-I Air blowout valve/winterizing kit.

LWS100 Low water shut-down.